

HYDRAINER

THE SUBMERSIBLE PUMP COMPANY

SPECIALIST HIRE OF HYDRAULIC AND ELECTRIC SUBMERSIBLE PUMPS

10 Series Silenced Diesel Power Pack



Features

- Baffled hydraulic oil reservoir with diffuser.
- Full flow return line filter with condition indicator & suction strainer.
- High pressure relief valve for maximum safety.
- Simple "ON/OFF" control.
- Automatic engine shut down for low oil level and automatic resetting excessive oil temperature.
- Handed quick release couplings to eliminate incorrect hose connection.
- Easily installed using non skilled labour.

Options

- Skid frames with roll over cages.
- Highway Trailer to full Road Traffic Act Regulations.
- Electric Drive for specialist industrial applications.
- GSM dialler for automatic phone notification of malfunction.

Engine

Type	-	Single Cylinder Air Cooled Hatz 1D81C Acoustic Diesel.
HP	-	9.0 h.p. – 6.7 kw continuous at 2000 rpm.
Speed	-	Governed to 2000 rpm off load.
Fuel Consumption	-	2.2 litres/hour at full load.
Fuel Pickup	-	Floating – eliminating silt pick up.
Starting	-	Full electric start as standard.
Noise Emission	-	On full load dB(A) @1m @5m @7m 74 71 67

Chassis

Fuel Tank	-	35 litres Approximately 16 hours consumption on full load.
Length	-	1575mm
Width	-	838mm
Height	-	1220mm
Weight	-	332kg full diesel tank.

Hydraulics

System	-	Open loop – 2 pipe.
Pump Type	-	Fixed displacement gear type.
Reservoir	-	35 litres.
Relief Valves	-	High pressure 150 bar-2200 psi.
Suction Filter	-	125 microns in reservoir.
Return Filter	-	Replacement elements to 25 microns.
Flow	-	20 l/min.
Pressure	-	Up to 136 bar-2000 psi.
Oil Grade	-	Mineral – ISO 46. Biodegradable – Hydra 46.
Oil Temperature	-	Max.80°C.

Hydraulic Hose

Length	-	10 and 20 metre sets.
Size	-	Flow & return 12mm dia.
Connection	-	Extendable up to 100 metres using bespoke Hydrainer quick release, double sealed locking couplings.

Contact details: www.hydrainer.com

Head Office: 0114 248 4868

