

SPECIALIST HIRE OF HYDRAULIC AND ELECTRIC SUBMERSIBLE PUMPS

30 Series Silenced Diesel Power Pack



Features

- Closed loop system for efficient compact power transmission & minimum volume of hydraulic oil.
- Enclosed in the reservoir, the variable displacement hydraulic pump gives the Hydrainer submersible pump variable impeller speeds.
- Full flow filters on flow & return lines for long component life.
- High & Low pressure relief valves for maximum safety.
- Simple adjustable ratchet handle controls.
- Automatic engine shut down for low oil level and automatic resetting excessive oil temperature.
- Handed quick release couplings to eliminate incorrect hose connection.
- Easily installed using non skilled labour.

Options

- Skid frames with roll over cages.
- Highway Trailer to full Road Traffic Act Regulations.
- Electric Drive for specialist industrial applications.
- GSM dialler for automatic phone notification of malfunction.
- Floats enable total automatic operation.

Engine

Hatz 3L41C Air Cooled Acoustic Type

Diesel.

ΗP 47 h.p. - 35 kw continuous at

2600 rpm.

Speed Governed to 2600 rpm off load. Fuel Consumption 11.5 litres/hour at full load.

Fuel Pickup Floating - eliminating silt pick

Starting Full electric start as standard.

Noise Emission On full load dB(A) @1m @5m @7m

98 86 83

Chassis

Fuel Tank 121 litres Approximately 11

hours consumption on full load.

Length 1702mm Width 990mm Height 1650mm

Weight 900kg full diesel tank.

Hydraulics

System Closed loop - 3 pipe.

Pump Type Variable displacement piston

with boost.

40 litres (approx.) Reservoir

High pressure 235 bar-3450 psi Relief Valves

Low pressure 29 bar-425 psi.

Suction Filter Spin on to 25 microns.

Return Filter Replacement elements to 10

microns.

Flow Up to 60 I/min.

Pressure Up to 205 bar-3000 psi. Oil Grade

Mineral - ISO 46.

Biodegradable - Hydra 46.

Oil Temperature Max.90°C.

Hydraulic Hose

10 and 20 metre sets. Length Flow & return 20mm dia., Size

drain 12mm dia.

Connection Extendable up to 100 metres using bespoke Hydrainer quick

release, double sealed locking

couplings.

Contact details: www.hydrainer.com

Head Office: 0114 248 4868

