HYDRAINER THE SUBMERSIBLE PUMP COMPANY


SPECIALIST HIRE OF HYDRAULIC AND ELECTRIC SUBMERSIBLE PUMPS

100 CP 25 Chopper Pump



Features

- Non-clog design by virtue of the chopping action of the sharpened impeller & cutting edges incorporated in the wear plate.
- Very high solids content is achieved without blocking the pump or discharge.
- Inherent mixing-the chopper design creates a mixing action thereby keeping the solids in suspension.
- Optional "breaker bar" breaks up larger solids, preventing blockages at the inlet.



Discharge Size	-	100 mm
Solids Size	-	50 mm
Weight	-	130 kg
Height	-	890 mm
Width (max.)	-	775 mm
Max. Head	-	32 m
Max. Output	-	72 l/s
H.P. Nominal	-	20 kw
Hydraulic Flow	-	60 l/min
Hydraulic Pressure		205 bar
Power Pack	-	30 Series
Construction		
Volute	-	GRADE 250 iron.
Impeller	-	SG iron.
Wear Plate	-	Adjustable mild steel with
	-	renewable steel wear face &
		incorporating 2 cutting edges.
Shaft Seal	-	Oil lubricated silicon carbide
		mechanical seal within metal
		bellows.
Shaft	-	EN57 stainless steel supported
		by robust oil lubricated
		bearings.
Motor	-	Gear motor incorporating
		Hydrainer high pressure shaft
		seal.

- Simple construction, requires little maintenance.
- Safe, no risk of electric shock or explosion.
- Runs dry mechanical shaft seal runs in an oil bath.
- Quiet, pump can be remote from power source.
- Spares & Service available through our national network.

Applications

Waste Disposal-pumping of rags, plastic bags, unscreened sewage. Industrial-Tank cleaning, transfer of mill scale, paint sluges etc... Food Waste-Processing of vegetable waste, bones, feathers & animal fleshings. Sludge Transfer-Digester cleaning & recirculation. Paper Mills-Pulp transfer. Agriculture-Farm effluent.

Contact details: <u>www.hydrainer.com</u> Head Office: 0114 248 4868

