

HYDRAINER

THE SUBMERSIBLE PUMP COMPANY

SPECIALIST HIRE OF HYDRAULIC AND ELECTRIC SUBMERSIBLE PUMPS

100 SH 25 Centrifugal Screw Pump




Discharge Size	-	100 mm
Solids Size	-	70 mm
Weight	-	150 kg
Height	-	1143 mm
Width (max.)	-	560 mm
Max. Head	-	38 m
Max. Output	-	56 l/s
H.P. Nominal	-	18.6 kw
Hydraulic Flow	-	60 l/min
Hydraulic Pressure	-	205 bar
Power Pack	-	30 Series

Construction

Volute	-	GRADE 250 iron.
Impeller & Liner	-	Cast iron as standard or high alloy wear resistant cast steel.
Shaft Seal	-	Oil lubricated silicon carbide mechanical seal.
Shaft	-	Stainless steel supported by robust oil lubricated preloaded bearings.
Motor	-	Gear motor incorporating Hydrainer high pressure shaft seal.

Features

- Solids handling – the screw centrifugal impeller has outstanding non-clog characteristics and will pump sludges & slurries beyond the capability of conventional centrifugal pumps.
- The axially extended impeller provides a smooth flow path between inlet & outlet & thus can handle more delicate and shear sensitive materials.
- High volume, high head, variable impeller speed.
- Simple construction, requires little maintenance.
- Easily portable.
- Safe, no risk of electric shock or explosion.
- Runs dry – mechanical shaft seal runs in an oil bath.
- Quiet, pump can be remote from power source.
- Spares & Service available through our national network.



Applications

- Agriculture Slurries
- Process Wastes
- Sewage Sludge
- Paper Mills
- Abattoir Waste
- Oil Refineries

Contact details: www.hydrainer.com

Head Office: 0114 248 4868

